



Aeliteflo

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision date: 6/26/2023 Supersedes: 1/19/2018 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Aeliteflo

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For Rx Only

1.3. Supplier

Manufacturer

BISCO, Inc.
1100 W. Irving Park Rd.
Schaumburg, IL , 60193
U.S.A.
T 1-800-247-3368 or 1-847-534-6000
sales@bisco.com - www.bisco.com

1.4. Emergency telephone number

Emergency number : CHEMTREC - 24-Hour Hazmat Emergency Communications Center
Domestic: 1-800-424-9300 Outside the U.S.: 1-703-527-3887, collect calls accepted

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin sensitization, Category 1 H317 May cause an allergic skin reaction
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning
Hazard statements (GHS US) : H317 - May cause an allergic skin reaction
Precautionary statements (GHS US) : P261 - Avoid breathing dust, fume, vapors.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302+P352 - If on skin: Wash with plenty of water and soap
P321 - Specific treatment (see First aid measures on this label)
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P501 - Dispose in a safe manner in accordance with local/national regulations

2.3. Other hazards which do not result in classification

No additional information available

Aeliteflo

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethoxylated Bis A Dimethacrylate	CAS-No.: 41637-38-1	10 - 30	Aquatic Chronic 4, H413
Triethylene Glycol Dimethacrylate	CAS-No.: 109-16-0	5 - 10	Skin Sens. 1B, H317
Polybutanediol Dimethacrylate 600	CAS-No.: 28883-57-0	5 - 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Tert-butyl Perbenzoate	CAS-No.: 614-45-9	< 1	Org. Perox. C, H242 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: May cause an allergic skin reaction.
-------------------------------------	--

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
------------------------------	----------------------------------

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust, fume, vapors.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust, fume, vapors. Wear personal protective equipment.
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Aeliteflo

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Paste.
Color	: Tooth
Odor	: Acrylic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: > 38 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: Not applicable
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
 Acute toxicity (dermal) : Not classified
 Acute toxicity (inhalation) : Not classified

Ethoxylated Bis A Dimethacrylate (41637-38-1)

LD50 oral rat	> 2000 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Read-across, Dermal, 15 day(s))

Triethylene Glycol Dimethacrylate (109-16-0)

LD50 oral rat	10837 mg/kg Source: NLM, THOMSON
LD50 dermal	> 2000 mg/kg body weight (US EPA, 14 day(s), Mouse, Male, Experimental value, Skin, 14 day(s))
ATE US (oral)	10837 mg/kg body weight

Polybutanediol Dimethacrylate 600 (28883-57-0)

LD50 oral rat	14500 mg/kg
ATE US (oral)	14500 mg/kg body weight

Tert-butyl Perbenzoate (614-45-9)

LD50 oral rat	1012 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Skin, 14 day(s))
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Not classified

Ethoxylated Bis A Dimethacrylate (41637-38-1)

pH	4.7 (< 0.01 %, 20 °C, OECD 105: Water Solubility)
----	---

Aeliteflo

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Triethylene Glycol Dimethacrylate (109-16-0)	
pH	6.8 - 7.2
Tert-butyl Perbenzoate (614-45-9)	
pH	No data available in the literature
Serious eye damage/irritation	: Not classified
Ethoxylated Bis A Dimethacrylate (41637-38-1)	
pH	4.7 (< 0.01 %, 20 °C, OECD 105: Water Solubility)
Triethylene Glycol Dimethacrylate (109-16-0)	
pH	6.8 - 7.2
Tert-butyl Perbenzoate (614-45-9)	
pH	No data available in the literature
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Polybutanediol Dimethacrylate 600 (28883-57-0)	
IARC group	4 - Probably not carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
Polybutanediol Dimethacrylate 600 (28883-57-0)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Triethylene Glycol Dimethacrylate (109-16-0)	
LOAEC (inhalation, rat, gas, 90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:
NOAEL (oral, rat, 90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, gas, 90 days)	100 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:
Tert-butyl Perbenzoate (614-45-9)	
NOAEL (oral, rat, 90 days)	≈ 30 mg/kg body weight Animal: rat, Guideline: other:
Aspiration hazard	: Not classified
Viscosity, kinematic	: Not applicable
Ethoxylated Bis A Dimethacrylate (41637-38-1)	
Viscosity, kinematic	No data available in the literature
Tert-butyl Perbenzoate (614-45-9)	
Viscosity, kinematic	No data available in the literature
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

SECTION 12: Ecological information**12.1. Toxicity**

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Ethoxylated Bis A Dimethacrylate (41637-38-1)	
LC50 - Fish [1]	> 100 mg/l Source: ECAH
EC50 72h - Algae [1]	> 100 mg/l Source: ECAH
Triethylene Glycol Dimethacrylate (109-16-0)	
LC50 - Fish [1]	16.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	72.8 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
LOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Tert-butyl Perbenzoate (614-45-9)	
LC50 - Fish [1]	1.6 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	11 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	0.8 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	0.8 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

Ethoxylated Bis A Dimethacrylate (41637-38-1)	
Persistence and degradability	Not readily biodegradable in water.
Triethylene Glycol Dimethacrylate (109-16-0)	
Persistence and degradability	Readily biodegradable in water.
Tert-butyl Perbenzoate (614-45-9)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.14 g O ₂ /g substance

12.3. Bioaccumulative potential

Ethoxylated Bis A Dimethacrylate (41637-38-1)	
Partition coefficient n-octanol/water (Log Pow)	5.62 (Practical experience/observation, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)

Aeliteflo

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethoxylated Bis A Dimethacrylate (41637-38-1)	
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).
Triethylene Glycol Dimethacrylate (109-16-0)	
Partition coefficient n-octanol/water (Log Pow)	2.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Tert-butyl Perbenzoate (614-45-9)	
Partition coefficient n-octanol/water (Log Pow)	3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Ethoxylated Bis A Dimethacrylate (41637-38-1)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.56 - 3.88 (log Koc, Calculated value)
Ecology - soil	Low potential for mobility in soil.
Triethylene Glycol Dimethacrylate (109-16-0)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.89 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
Tert-butyl Perbenzoate (614-45-9)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.3 (log Koc, QSAR, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable

Aeliteflo

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Aeliteflo

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

Ethoxylated Bis A Dimethacrylate (41637-38-1)

Listed on the Canadian DSL (Domestic Substances List)

Triethylene Glycol Dimethacrylate (109-16-0)

Listed on the Canadian DSL (Domestic Substances List)

Polybutanediol Dimethacrylate 600 (28883-57-0)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Tert-butyl Perbenzoate (614-45-9)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Triethylene Glycol Dimethacrylate (109-16-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Tert-butyl Perbenzoate(614-45-9)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 06/26/2023

Full text of H-phrases

H242	Heating may cause a fire.
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects

Aeliteflo

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases

H413	May cause long lasting harmful effects to aquatic life
------	--

Indication of changes:

Section	Changed item	Change	Comments
	Revision date	Added	
	Signal word (GHS US)	Added	
	Precautionary statements (GHS US)	Modified	
	Hazard statements (GHS US)	Modified	
	Supersedes	Added	
	Issue date	Removed	
2.1	GHS-US classification	Modified	
3	Composition/Information on ingredients	Modified	
5.2	Hazardous decomposition products in case of fire	Modified	

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.